

## **D3.4\_PHPP Result Sheets**

**DRAFT**

**CS01**

**Home for Elderly, Dun Laoghaire**

**INTELLIGENT ENERGY – EUROPE II**

Energy efficiency and renewable energy in buildings

IEE/12/070

**EuroPHit**

[Improving the energy performance of step-by-step refurbishment and integration of renewable energies]

Contract N°: SI2.645928



Co-funded by the Intelligent Energy Europe  
Programme of the European Union

## Technical References

Project Acronym	EuroPHit
Project Title	Improving the energy performance of step-by-step refurbishment and integration of renewable energies
Project Coordinator	Jan Steiger Passive House Institute, Dr. Wolfgang Feist Rheinstrasse 44/46 D 64283 Darmstadt jan.steiger@passiv.de
Project Duration	1 April 2013 – 31 March 2016 (36 Months)

Deliverable No.	D3.4
Dissemination Level	PU
Work Package	WP3_Practical Implementation
Lead beneficiary	04_MosArt
Contributing beneficiary(ies)	CB4, MosArt
Author(s)	Mariana Moreira
Co-author(s)	Art McCormack
Date	24 11 2014
File Name	EuroPHit_D3.4_CS01_20140623_MosArt_Home for Elderly_Dun Laoghaire.doc

The sole responsibility for the content of this [webpage, publication etc.] lies with the authors. It does not necessarily reflect the opinion of the European Union. Neither the EACI nor the European Commission are responsible for any use that may be made of the information contained therein.



## Table of Contents

Abstract	4
1 Existing building: PHPP Result Sheet	5
1.1 PHPP Result sheet of the existing building	5
2 Retrofit steps	6
2.1 Overall refurbishment Plan	6
2.1.1 Retrofit steps:	6
2.1.2 Efficiency Improvements	6
3 Completion of step-by-step refurbishment to EnerPHit	7
3.1 PHPP Result Sheet of the completed EnerPHit standard	7

## List of tables and figures

Figure 1: Specific energy efficiency values of the existing building modelled with PHPP 9 Beta	5
Figure 2: Overview refurbishment steps	6
Figure 3: Overview energy efficiency improvement according to the overall refurbishment plan	6
Figure 4: Specific energy efficiency values of the completed project modelled with PHPP 9 Beta	7



## Abstract

This overall refurbishment plan provides an overview of the retrofit steps of a step-by-step refurbishment to EnerPHit standard to be undertaken for the project Home for Elderly.

First, the existing building will shortly be described, including building component and component conditions. In addition, the existing energy efficiency performance of the building will be described.

In a second step, the overall refurbishment plan will describe the retrofit steps to be undertaken until the refurbishment will finally be completed. The EnerPHit standard will be achieved by: a) externally insulate the existing walls; b) replace existing double glazed windows to passive house windows; c) carefully airtight the building at each junction and fully plaster the external walls, d) heat recovery ventilation unit for each apartment, community areas and circulation areas; e) install a micro CHP (combined heat and power) with gas condenser boiler connected to radiators installed throughout the building.




Figure 1: Northwest view [MosArt, 2013]



# 1 Existing building: PHPP Result Sheet

## 1.1 PHPP Result sheet of the existing building

EnerPHit verification				
		Building: <b>Block One Rochestown House</b>		
		Street: <b>Sallynogin Road Upper</b>		
		Postcode/City: <b>Dún Laoghaire</b>		
		Country: <b>Ireland</b>		
Building type: <b>Home for Elderly</b>		Climate: <b>[IE] - Dublin</b>		
Altitude of building site (in [m] above sea level):		-		
Home owner/client: <b>DLR CC</b>		Street: <b>Dún Laoghaire</b>		
Postcode/City: <b>Dún Laoghaire</b>		Mechanical System:		
Architecture: <b>DLR CC</b>		Street:		
Street: <b>Dún Laoghaire</b>		Postcode/City:		
Postcode/City: <b>Dún Laoghaire</b>		Certification:		
Energy consulting:		Street:		
Street:		Postcode/City:		
Postcode/City:				
Year of Construction:	<b>1960</b>	Interior temperature winter [C°]	<b>20.0</b>	
Number of dwelling units:	<b>34</b>	Internal heat gains winter [W/m²]	<b>4.1</b>	
Number of Occupants:	<b>48.1</b>	Interior temp. summer [C°]	<b>25.0</b>	
Exterior vol. V <sub>e</sub> :	<b>6339.6</b> m³	IHG summer [W/m²]	<b>4.1</b>	
		Spec. capacity [Wh/K per m² TFA]	<b>204</b>	
		Mechanical cooling:		
Specific building demands with reference to the treated floor area				
Treated floor area		<b>1613.3</b> m²		
Space heating	Annual heating demand	<b>354.08</b> kWh/(m²a)	25 kWh/(m²a)	
	Heating load	<b>110</b> W/m²	-	
Space cooling	Overall specific space cooling demand	<b>kWh/(m²a)</b>	-	
	Cooling load	<b>W/m²</b>	-	
	Frequency of overheating (> 25 °C)	<b>0.0</b> %	-	
Primary Energy	Heating, cooling, dehumidifying, DHW,	<b>688</b> kWh/(m²a)	527 kWh/(m²a)	
	DHW, space heating and auxiliary electricity	<b>604</b> kWh/(m²a)	-	
	Specific primary energy reduction through solar electricity	<b>kWh/(m²a)</b>	-	
Airtightness	Pressurization test result n <sub>50</sub>	<b>5.0</b> 1/h	1 1/h	
EnerPHit (Modernisierung): Bauteilkennwerte				
Gebäudehülle	Außendämmung zu Außenluft	<b>4.05</b> W/(m²K)	-	
	mittlere U-Werte	Außendämmung zu Erdreich	<b>3.85</b> W/(m²K)	-
		Innendämmung zu Außenluft	<b>W/(m²K)</b>	-
		Innendämmung zu Erdreich	<b>W/(m²K)</b>	-
		Wärmebrücken ΔU	<b>0.00</b> W/(m²K)	-
	Fenster	<b>1.71</b> W/(m²K)	-	
Außentüren		<b>W/(m²K)</b>	-	
Lüftungsanlage		eff. Wärmebereitstellungsgrad	<b>%</b>	-

\* empty field: data missing; -: no requirement

Figure 2: Specific energy efficiency values of the existing building modelled with PHPP 9 Beta



## 2 Retrofit steps

### 2.1 Overall refurbishment Plan

#### 2.1.1 Retrofit steps:

This Client is willing to complete the EnerPHit standard refurbishment of this building in one phase – the first refurbishment step that includes the additional floor, entrance area and vertical circulation area to Passive House standards and the refurbishment of existing walls, windows and door. We propose that a Solar hot water system will be installed on the roof by 2020, as the second phase of the refurbishment of this building.

Step No.	Year	Measures	Specific Heating Demand [kWh/m <sup>2</sup> a]	Specific Primary Energy Demand [kWh/m <sup>2</sup> a]	Additional Specific PV Gains
1	1960	Existing Building	354	688	
2	2014	EnerPHit standard refurbishment	24	109	
3	2020	Solar Panels	24	95	0

Figure 3: Overview refurbishment steps

#### 2.1.2 Efficiency Improvements






Figure 4: Overview energy efficiency improvement according to the overall refurbishment plan





### 3 Completion of step-by-step refurbishment to EnerPHit

#### 3.1 PHPP Result Sheet of the completed EnerPHit standard

EnerPHit verification					
 Northwest Facing Elevation		Building: <b>Block One Rochestown House</b> Street: <b>Sallynogin Road Upper</b> Postcode/City: <b>Dún Laoghaire</b> Country: <b>Ireland</b> Building type: <b>Home for Elderly</b> Climate: <b>[IE] - Dublin</b> Altitude of building site (in [m] above sea level): <b>-</b>			
 Southeast Facing Elevation		Home owner/client: <b>DLR CC</b> Street: <b>Dún Laoghaire</b> Postcode/City: <b>Dún Laoghaire</b>			
Architecture: <b>DLR CC</b> Street: <b>Dún Laoghaire</b> Postcode/City: <b>Dún Laoghaire</b>		Mechanical System: Street: Postcode/City:			
Energy consulting: Street: Postcode/City:		Certification: Street: Postcode/City:			
Year of Construction: <b>2015</b> Number of dwelling units: <b>34</b> Number of Occupants: <b>53.0</b> Exterior vol. $V_{e,0}$ : <b>6339.6</b> m <sup>3</sup>		Interior temperature winter [C°]: <b>20.0</b> Internal heat gains winter [W/m²]: <b>4.1</b> Interior temp. summer [C°]: <b>25.0</b> IHG summer [W/m²]: <b>4.1</b> Spec. capacity [Wh/K per m² TFA]: <b>204</b> Mechanical cooling:			
Specific building demands with reference to the treated floor area					
		Treated floor area	Requirements	Fulfilled?*	
<b>Space heating</b>	Annual heating demand	<b>23.72</b> kWh/(m²a)	25 kWh/(m²a)	<b>yes</b>	
	Heating load	<b>13</b> W/m²	-	-	
	Overall specific space cooling demand	<b>kWh/(m²a)</b>	-	-	
<b>Space cooling</b>	Cooling load	<b>W/m²</b>	-	-	
	Frequency of overheating (> 25 °C)	<b>0.0</b> %	-	-	
<b>Primary Energy</b>	Heating, cooling, dehumidifying, DHW,	<b>109</b> kWh/(m²a)	130 kWh/(m²a)	<b>yes</b>	
	DHW, space heating and auxiliary electricity	<b>38</b> kWh/(m²a)	-	-	
	Specific primary energy reduction through solar electricity	<b>kWh/(m²a)</b>	-	-	
<b>Airtightness</b>	Pressurization test result $n_{50}$	<b>1.0</b> 1/h	1 1/h	<b>yes</b>	
EnerPHit (Modernisierung): Bauteilkennwerte					
<b>Gebäudehülle</b>	Außendämmung zu Außenluft	<b>0.14</b> W/(m²K)	-	-	
	mittlere U-Werte	Außendämmung zu Erdreich	<b>3.74</b> W/(m²K)	-	-
		Innendämmung zu Außenluft	<b>W/(m²K)</b>	-	-
	Innendämmung zu Erdreich	<b>W/(m²K)</b>	-	-	
	Wärmebrücken $\Delta U$	<b>0.00</b> W/(m²K)	-	-	
	Fenster	<b>1.00</b> W/(m²K)	-	-	
	Außentüren	<b>W/(m²K)</b>	-	-	
	<b>Lüftungsanlage</b>	eff. Wärmebereitstellungsgrad	<b>78</b> %	-	-

\* empty field: data missing; -: no requirement

Figure 5: Specific energy efficiency values of the completed project modelled with PHPP 9 Beta

