

D3.4_PHPP Result Sheets

DRAFT

CS12

Family Home_Ville & Andrea Mäkinen

INTELLIGENT ENERGY – EUROPE II

Energy efficiency and renewable energy in buildings

IEE/12/070

EuroPHit

[Improving the energy performance of step-by-step refurbishment and integration of renewable energies]

Contract N°: SI2.645928



Co-funded by the Intelligent Energy Europe
Programme of the European Union

Technical References

Project Acronym	EuroPHit
Project Title	Improving the energy performance of step-by-step refurbishment and integration of renewable energies
Project Coordinator	Jan Steiger Passive House Institute, Dr. Wolfgang Feist Rheinstrasse 44/46 D 64283 Darmstadt jan.steiger@passiv.de
Project Duration	1 April 2013 – 31 March 2016 (36 Months)

Deliverable No.	D3.4
Dissemination Level	PU
Work Package	WP3_Practical Implementation
Lead beneficiary	04_MosArt
Contributing beneficiary(ies)	06 IGPH
Author(s)	Ingo Theoboldt
Co-author(s)	
Date	30-11-2014
File Name	EuroPHit_D3.4_CS12_20141130_IGPH_Family Home_Ville & Andrea Mäkinen.doc

The sole responsibility for the content of this [webpage, publication etc.] lies with the authors. It does not necessarily reflect the opinion of the European Union. Neither the EACI nor the European Commission are responsible for any use that may be made of the information contained therein.



Table of Contents

Abstract	4
1 Existing building: PHPP Result Sheet	5
1.1 PHPP Result sheet of the existing building	5
2 Retrofit steps	6
2.1 Overall refurbishment Plan	6
2.1.1 Retrofit steps:	6
2.1.2 Efficiency Improvements	7
3 Completion of step-by-step refurbishment to EnerPHit	8
3.1 PHPP Result Sheet of the completed EnerPHit standard	8

List of tables and figures


Figure 1: Specific energy efficiency values of the existing building modelled with PHPP	5
Figure 2: Overview refurbishment steps	6
Figure 3: Overview energy efficiency improvement according to the overall refurbishment plan	7
Figure 4: Specific energy efficiency values of the completed project modelled with PHPP	8

Abstract


This document provides a short overview of the efficiency improvement of a step-by-step refurbishment to EnerPHit standard to be undertaken for the project 12, Family Home Ville & Andrea Mäkinen in Stockholm, Sweden.

First, the result sheet of the project's current status will present the calculated energy consumption of the existing building.

The PHPP result sheet of the completed EnerPHit retrofit will present the energy demand estimated for the completion of the project according to the overall refurbishment plan




KÄLLARPLAN



BOTTENPLAN

Existing building: PHPP Result Sheet

1.1 PHPP Result sheet of the existing building

EnerPHit verification				
		Building:	Ville & Andrea Mäkinen	
		Street:	Svartbäcksvägen 11	
		Postcode/City:	Stockholm	
		Country:	Sweden	
		Building type:	Villa	
		Climate:	[SE] - Stockholm	
		Altitude of building site (in [m] above sea level): 50		
		Home owner/client:	Ville	
		Street:	Svartbäcksvägen 11	
		Postcode/City:	Stockholm	
Architecture:		Mechanical System:		
Street:		Street:		
Postcode/City:		Postcode/City:		
Energy consulting:		Certification:		
Street:		Street:		
Postcode/City:		Postcode/City:		
Year of Construction:	1955	Interior temperature winter [C°]	20.0	
Number of dwelling units:	1	Interior temp. summer [C°]	25.0	
Number of Occupants:	4.3	Internal heat gains winter [W/m²]	2.1	
Exterior vol. V _e :	408.0 m³	IHG summer [W/m²]	3.1	
		Spec. capacity [Wh/K per m² TFA]	204	
		Mechanical cooling:		
Specific building demands with reference to the treated floor area				
Treated floor area		150.1 m²		
Space heating	Annual heating demand	235 kWh/(m²a)	25 kWh/(m²a)	
	Heating load	77 W/m²	-	
Space cooling	Overall specific space cooling demand	kWh/(m²a)	-	
	Cooling load	W/m²	-	
	Frequency of overheating (> 25 °C)	0.0 %	-	
Primary Energy	heating, cooling, ventilation, DHW, auxiliary electricity, lighting, etc.	256 kWh/(m²a)	384 kWh/(m²a)	
	DHW, space heating and auxiliary electricity	194 kWh/(m²a)	-	
	Specific primary energy reduction through solar electricity	kWh/(m²a)	-	
Airtightness	Pressurization test result n ₅₀	4.4 1/h	1 1/h	
EnerPHit (Modernisierung): Bauteilkennwerte				
Gebäudehülle	Außendämmung zu Außenluft	0.76 W/(m²K)	-	
	mittlere U-Werte	Außendämmung zu Erdreich	3.34 W/(m²K)	-
		Innendämmung zu Außenluft	W/(m²K)	-
		Innendämmung zu Erdreich	W/(m²K)	-
		Wärmebrücken ΔU	0.00 W/(m²K)	-
	Fenster	2.26 W/(m²K)	-	
	Außentüren	2.00 W/(m²K)	-	
Lüftungsanlage	eff. Wärmebereitstellungsgrad	%	-	

* empty field: data missing; -: no requirement

Figure 1: Specific energy efficiency values of the existing building modelled with PHPP

2 Retrofit steps

2.1 Overall refurbishment Plan

2.1.1 Retrofit steps:

Wilmcote house will be enclosed in an insulated self-supporting steel skeleton to improve the thermal performance of the walls, roof, windows and doors. New heat recovery ventilation systems will be provided for each flat. Existing heating systems will be retained for the time being.

Step No.	Year	Measures	Specific Heating demand [kWh/(m ² K)]	Specific PE demand [kWh/(m ² K)]
0	1954	Existing building	235	256
1	2014-15	Replace lower floor & add roof insulation; insulate lower floor walls	111	153
2	2016 (?)	Windows exchange & MVHR instal.	71	124
3	2020 (?)	Upper floor facade insulation	17 ^{*)}	85
4	2020 (?)	Possible addition of PV and/or solar thermal system	-	65 ^{**)}

^{*)} EnerPhit-certification via components not necessary

^{**)} Approx. estimate e.g. with a 3.3 kWp PV system

Figure 2: Overview refurbishment steps

2.1.2 Efficiency Improvements




Figure 3: Overview energy efficiency improvement according to the overall refurbishment plan

3 Completion of step-by-step refurbishment to EnerPHit

3.1 PHPP Result Sheet of the completed EnerPHit standard

	Treated floor area	150.1 m ²		
Space heating	Annual heating demand	17 kWh/(m ² a)	Requirements 25 kWh/(m ² a)	Fulfilled?*
	Heating load	11 W/m ²	-	-
Space cooling	Overall specific space cooling demand	kWh/(m ² a)	-	-
	Cooling load	W/m ²	-	-
	Frequency of overheating (> 25 °C)	8.0 %	-	-
Primary Energy	meanly, cooling, ventilation, DHW, auxiliary electricity	85 kWh/(m ² a)	122 kWh/(m ² a)	yes
	DHW, space heating and auxiliary electricity	32 kWh/(m ² a)	-	-
	Specific primary energy reduction through solar electricity	kWh/(m ² a)	-	-
Airtightness	Pressurization test result n ₅₀	1.0 1/h	1 1/h	yes
EnerPHit (Modernisierung): Bauteilkennwerte				
Gebäudehülle mittlere U-Werte	Außendämmung zu Außenluft	0.09 W/(m ² K)	-	-
	Außendämmung zu Erdreich	0.09 W/(m ² K)	-	-
	Innendämmung zu Außenluft	W/(m ² K)	-	-
	Innendämmung zu Erdreich	W/(m ² K)	-	-
	Wärmebrücken ΔU	0.00 W/(m ² K)	-	-
	Fenster	0.89 W/(m ² K)	-	-
Lüftungsanlage	Außentüren	0.80 W/(m ² K)	-	-
	eff. Wärmebereitstellungsgrad	83 %	-	-

Figure 4: Specific energy efficiency values of the completed project modelled with PHPP